

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000870

International filing date: 07 March 2005 (07.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0405015.9
Filing date: 05 March 2004 (05.03.2004)

Date of receipt at the International Bureau: 21 April 2005 (21.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Andrew Gersey

Signed

Dated 30 March 2005

Patents Form 1/77

Patents Act 1977
(Rule 16)05MAR04 E879710-1 001091
F01/7700 0.00-0405015.9 NONE**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

AA 1692 GB

2. Patent application number

(The Patent Office will fill in this part)

0405015.9

- 5 MAR 2004

3. Full name, address and postcode of the or of each applicant (underline all surnames)

JOHNSON MATTHEY PUBLIC LIMITED
COMPANY,
2-4 COCKSPUR STREET,
TRAFALGAR SQUARE,
LONDON SW1Y 5BQ 536268010
UK

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

METHOD OF LOADING A MONOLITH WITH CATALYST AND/OR
WASHCOAT

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

ANDREW DOMINIC NUNN

JOHNSON MATTHEY TECHNOLOGY
CENTRE,
BLOUNT'S COURT,
JANNING COMMON,
READING RG4 9NH 3991411001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d).

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawing(s)

3
1
1
0

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Andrew

Date

5/3/04

12. Name and daytime telephone number of person to contact in the United Kingdom

MRS. F. E. STRANGE

0118 924 2125

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

AA 1692

**METHOD OF LOADING A MONOLITH WITH CATALYST AND/OR
WASHCOAT**

5 The present invention relates to a method of loading a monolith with a catalyst and/or a washcoat and in particular to a method of inserting the catalyst and/or washcoat in the pore structure of the monolith.

10 It is known to load a catalyst and/or a washcoat on a honeycomb monolith such as a ceramic flow-through monolith or wall-flow filter. The resulting piece is then dried and calcined to make the desired product. See for example our PCT application claiming priority from GB 0304939.2.

15 A washcoat is generally a slurry comprising a high surface area particulate refractory oxide such as bulk ceria, silica, alumina, titania, zirconia, or a mixed oxide or composite oxide of any two or more thereof, e.g. ceria-zirconia, silica-alumina etc. The washcoat and/or the refractory oxide particles can include an active catalytic metal compound such as a platinum group metal, e.g. platinum, palladium or rhodium, or a molten salt to promote soot combustion e.g. an alkali metal salt or a lanthanum salt of vanadium, tungsten or molybdenum or vanadium pentoxide.

20 By "composite oxide" herein, we mean a largely amorphous oxide material comprising oxides of at least two elements which are not true mixed oxides consisting of at least two metals.

25 Alternatively, the monolith material itself can be impregnated with a suitable aqueous salt of any of the above metals and the resulting piece is then dried and calcined. Of course, a washcoated monolith that has been dried can also be impregnated using this method.

30 A typical wall-flow filter has a shape of a honeycomb, the honeycomb having an inlet end and an outlet end, and a plurality of cells extending from the inlet end to the outlet end, the cells having porous walls wherein part of the total number of cells at the inlet end are plugged along a portion of their lengths, and the remaining part of the cells

that are open at the inlet end are plugged at the outlet end along a portion of their lengths, so that a flowing exhaust gas stream passing through the cells of the honeycomb from the inlet end flows into the open cells, through the cell walls, and out of the filter through the open cells at the outlet end.

5

Ceramic materials for flow-through monoliths and wall-flow filters are typically made of at least one of silicon, silicon carbide, aluminium nitride, silicon nitride, aluminium titanate, alumina, cordierite, mullite, sillimanite or a thermocouple such as $\text{Al}_2\text{O}_3/\text{Fe}$, $\text{Al}_2\text{O}_3/\text{Ni}$ or $\text{B}_4\text{C}/\text{Fe}$.

10

It is also known that catalysed soot filters require more porosity and generally larger pore sizes to non-catalysed filters to enable coating with catalyst systems. In order to have acceptably low pressure losses after being coated with the catalyst/washcoat systems at about 50 g/dm^3 loading. Typical porosity is usually from about 45-55%.

15 Where the catalyst system comprises a NO_x storage/reduction system, higher washcoat loadings are required, possibly above 100 g/dm^3 . In this embodiment, filter substrate porosity may be above 60%.

One method of loading the pore structure of a wall-flow filter is disclosed in EP 0766993. One end of a honeycomb monolith is alternately plugged as described above. The plugged end is labelled the exhaust gas outlet end and is disposed with the plugged end uppermost. A washcoat composition is applied to plugged end which flows down the channels and permeates into the porous walls due to capillarity. To facilitate this process, the coating solution may be sucked through the monolith under vacuum. The resulting piece is dried, the other end of the monolith is plugged to generate a wall-flow filter having the above described structure.

We have considered this method and do not believe it is of practical utility for a number of reasons. Firstly, the method is very labour intensive requiring a number of separate steps in order to generate the desired piece. For example, a better method would load a catalyst and/or washcoat on an unloaded wall-flow filter, i.e. wherein both ends are already plugged. Secondly, the use of a vacuum does not guarantee insertion of the desired washcoat components in the pore structure of the filter. In particular, we have found that

by applying a vacuum washcoat components can build up in a cake, preventing satisfactory ingress of the desired components into the pore structure of the monolith. However, relying on capillarity to introduce washcoat components in the pore structure, particularly for more viscous washcoats, is time intensive.

5

We have now developed a method of loading a monolith with a catalyst and/or a washcoat wherein the problems associated with this prior art are reduced or avoided. In one embodiment the method is of particular utility to wall-flow filters, although the method can also be used with advantage for loading through-flow monolith substrates.

10

According to one aspect, the invention provides a method of loading a monolith with a catalyst and/or a washcoat, which method comprising introducing the monolith into a closeable enclosure, applying a vacuum to the enclosure to withdraw gas from a pore structure of the monolith and introducing a liquid comprising the catalyst and/or washcoat into the vacuated enclosure to insert the catalyst and/or washcoat in the monolith pore structure.

15

An advantage of the present invention is that, by removing the air from the pore structure of the monolith, we have found that the ingress of liquid is greatly facilitated.

20

In a further aspect the invention provides an apparatus for carrying out the method according to the invention, comprising a closeable enclosure and means for introducing a liquid into the vacuated enclosure.

25



CLAIMS:

1. A method of loading a monolith with a catalyst and/or a washcoat, which method
comprising introducing the monolith into a closeable enclosure, applying a vacuum
to the enclosure to withdraw gas from a pore structure of the monolith and
introducing a liquid comprising the catalyst and/or washcoat into the vacuated
enclosure to insert the catalyst and/or washcoat in the monolith pore structure.
2. Apparatus for carrying out the method according to claim 1, comprising a closeable
enclosure and means for introducing a liquid into the vacuated enclosure.

ABSTRACT**METHOD OF LOADING A MONOLITH WITH CATALYST AND/OR WASHCOAT**

5 A method of loading a monolith with a catalyst and/or a washcoat comprises introducing the monolith into a closeable enclosure, applying a vacuum to the enclosure to withdraw gas from a pore structure of the monolith and introducing a liquid comprising the catalyst and/or washcoat into the vacuated enclosure to insert the catalyst and/or washcoat in the monolith pore structure. An apparatus for carrying out the method comprises a closeable enclosure and means
10 for introducing a liquid into the vacuated enclosure.



